



DECLARATION OF PERFORMANCE

No. 001GCR2013

1. Unique identification code of the product type

Type, batch or serial number or any other element allowing identification of the product

Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$

2. Intended use(s)

For internal and external walls and floorings

3. Name or registered trade mark, and contact address of the manufacturer

GRUPPO CERAMICHE RICCHETTI SpA - via Statale 118/M - 42013 Casalgrande (RE)

4. System(s) of assessment and verification of constancy of performance (AVCP)

N.A.

5. Name and identification number of notified laboratory, if relevant

N.A.

6. Declared Performances

Essential characteristics	Performance	Harmonised Specifications
Reaction to fire	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength, thickness $\geq 7,5$ mm	> 1.300 N	
Breaking strength, thickness $\leq 7,5$ mm	> 700 N	
Slipperiness	See table attached	
Tactility	NDP	
Bond strength/adhesion, for		
Cementitious adhesive, type C2	NDP	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The Performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Claudio De Pietri - Quality Assurance
name and function

Maranello 19/06/2013

Place and date of issue

Signature